



Trade name: Marabu-GlasArt 400, 50 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130205400

Replaces Version: 6 / GB

Print date: 10.03.16

## **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

### **1.1. Product identifier**

Marabu-GlasArt 400, 50 ml

### **1.2. Relevant identified uses of the substance or mixture and uses advised against**

#### **Use of the substance/preparation**

Paint

### **1.3. Details of the supplier of the safety data sheet**

#### **Address**

Marabu GmbH & Co. KG  
Asperger Strasse 4  
71732 Tamm  
Germany  
Telephone no. +49-7141/691-0  
Fax no. +49-7141/691-147  
Information provided by / telephone Department product safety  
E-mail address of person responsible PRSI@marabu.de  
for this SDS

### **1.4. Emergency telephone number**

(+49) (0)621-60-43333

## **SECTION 2: Hazards identification \*\*\***

### **2.1. Classification of the substance or mixture**

#### **Classification (Regulation (EC) No. 1272/2008)**

Classification (Regulation (EC) No. 1272/2008)  
Flam. Liq. 3 H226  
STOT SE 3 H336

### **2.2. Label elements**

#### **Labelling according to regulation (EC) No 1272/2008**

##### **Hazard pictograms**



##### **Signal word**

Warning

##### **Hazard statements \*\*\***

H226 Flammable liquid and vapour.  
H336 May cause drowsiness or dizziness.

##### **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition



Trade name: Marabu-GlasArt 400, 50 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130205400

Replaces Version: 6 / GB

Print date: 10.03.16

P271 sources. No smoking.  
 Use only outdoors or in a well-ventilated area.  
 P405 Store locked up.  
 P501.9 Dispose of contents/container as problematic waste.

**Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)**

contains \*\*\* 1-Methoxy-2-propanol;Naphtha (petroleum), hydrotreated heavy

**Supplemental information**

EUH066 Repeated exposure may cause skin dryness or cracking.

**2.3. Other hazards**

No special hazards have to be mentioned.

**SECTION 3: Composition/information on ingredients \*\*\*****3.2. Mixtures****Chemical characterization**

Paint based on alkyd resins and on solvents

**Hazardous ingredients \*\*\*****1-Methoxy-2-propanol**

|                  |                  |   |    |  |   |
|------------------|------------------|---|----|--|---|
| CAS No.          | 107-98-2         |   |    |  |   |
| EINECS no.       | 203-539-1        |   |    |  |   |
| Registration no. | 01-2119457435-35 |   |    |  |   |
| Concentration    | >= 25            | < | 50 |  | % |

Classification (Regulation (EC) No. 1272/2008)  
 STOT SE 3 H336  
 Flam. Liq. 3 H226

**Naphtha (petroleum), hydrotreated heavy**

|                  |                  |   |    |  |   |
|------------------|------------------|---|----|--|---|
| CAS No.          | 64742-48-9       |   |    |  |   |
| EINECS no.       | 919-857-5        |   |    |  |   |
| Registration no. | 01-2119463258-33 |   |    |  |   |
| Concentration    | >= 10            | < | 20 |  | % |

Classification (Regulation (EC) No. 1272/2008)  
 Asp. Tox. 1 H304  
 Flam. Liq. 3 H226  
 STOT SE 3 H336  
 EUH066

**2-Butoxyethyl acetate**

|                  |                  |   |    |  |   |
|------------------|------------------|---|----|--|---|
| CAS No.          | 112-07-2         |   |    |  |   |
| EINECS no.       | 203-933-3        |   |    |  |   |
| Registration no. | 01-2119475112-47 |   |    |  |   |
| Concentration    | >= 1             | < | 10 |  | % |

Classification (Regulation (EC) No. 1272/2008)  
 Acute Tox. 4 H332  
 Acute Tox. 4 H312  
 Acute Tox. 4 H302

**Hexanoic acid, 2-ethyl-, zinc salt, basic**

|                  |                  |  |  |  |  |
|------------------|------------------|--|--|--|--|
| CAS No.          | 85203-81-2       |  |  |  |  |
| EINECS no.       | 286-272-3        |  |  |  |  |
| Registration no. | 01-2119979093-30 |  |  |  |  |



Trade name: Marabu-GlasArt 400, 50 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130205400

Replaces Version: 6 / GB

Print date: 10.03.16

|               |    |     |   |   |   |
|---------------|----|-----|---|---|---|
| Concentration | >= | 0,1 | < | 1 | % |
|---------------|----|-----|---|---|---|

Classification (Regulation (EC) No. 1272/2008)

|                   |       |
|-------------------|-------|
| Eye Irrit. 2      | H319  |
| Repr. 2           | H361d |
| Aquatic Chronic 3 | H412  |

## **SECTION 4: First aid measures**

### **4.1. Description of first aid measures**

#### **General information**

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

#### **After inhalation**

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

#### **After skin contact**

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

#### **After eye contact**

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

#### **After ingestion**

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

### **4.2. Most important symptoms and effects, both acute and delayed**

Until now no symptoms known so far.

### **4.3. Indication of any immediate medical attention and special treatment needed**

#### **Hints for the physician / treatment**

Treat symptomatically

## **SECTION 5: Firefighting measures**

### **5.1. Extinguishing media**

#### **Suitable extinguishing media**

Recommended: alcohol resistant foam, CO<sub>2</sub>, powders, water spray/mist, Not be used for safety reasons: water jet

### **5.2. Special hazards arising from the substance or mixture**

In the event of fire the following can be released: Carbon monoxide (CO); Carbon dioxide (CO<sub>2</sub>); dense black smoke; Nitrogen oxides (NO<sub>x</sub>)

### **5.3. Advice for firefighters**

#### **Special protective equipment for fire-fighting**

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses.

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective



Trade name: Marabu-GlasArt 400, 50 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130205400

Replaces Version: 6 / GB

Print date: 10.03.16

measures listed in Sections 7 and 8.

## 6.2. Environmental precautions

Do not allow to enter drains or waterways. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

## 6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

## 6.4. Reference to other sections

Information regarding Safe handling, see Section 7. Information regarding personal protective measures, see Section 8. Information regarding waste disposal, see Section 13.

# **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

### Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Avoid skin and eye contact. Avoid the inhalation of particulates and spray mist arising from the application of this mixture. Smoking, eating and drinking shall be prohibited in application area. For personal protection see Section 8. Never use pressure to empty: container is not a pressure vessel. Always keep in containers of same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or water courses.

### Advice on protection against fire and explosion

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

### Classification of fires / temperature class / Ignition group / Dust explosion class

|                         |                                   |
|-------------------------|-----------------------------------|
| Classification of fires | B (Combustible liquid substances) |
| Temperature class       | T4                                |

## 7.2. Conditions for safe storage, including any incompatibilities

### Requirements for storage rooms and vessels

Electrical installations/working materials must comply with the local applied technological safety standards. Storage rooms in which filling operations take place must have a conducting floor. Store in accordance with national regulation

### Hints on storage assembly

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

### Further information on storage conditions

Observe label precautions. Store between 15 and 30 °C in a dry, well ventilated place away from sources of heat and direct sunlight. Keep container tightly closed. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

## 7.3. Specific end use(s)

Paint

# **SECTION 8: Exposure controls/personal protection \*\*\***

## 8.1. Control parameters



Trade name: Marabu-GlasArt 400, 50 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130205400

Replaces Version: 6 / GB

Print date: 10.03.16

**Exposure limit values \*\*\*****1-Methoxy-2-propanol**

|                                                     |      |                   |     |        |
|-----------------------------------------------------|------|-------------------|-----|--------|
| List                                                | EH40 |                   |     |        |
| Type                                                | WEL  |                   |     |        |
| Value                                               | 375  | mg/m <sup>3</sup> | 100 | ppm(V) |
| Short term exposure limit                           | 560  | mg/m <sup>3</sup> | 150 | ppm(V) |
| Skin resorption / sensibilisation: Sk; Status: 2011 |      |                   |     |        |

**2-Butoxyethyl acetate**

|                                                     |      |  |    |        |
|-----------------------------------------------------|------|--|----|--------|
| List                                                | EH40 |  |    |        |
| Type                                                | WEL  |  |    |        |
| Value                                               | 133  |  | 20 | ppm(V) |
| Short term exposure limit                           | 332  |  | 50 | ppm(V) |
| Skin resorption / sensibilisation: Sk; Status: 2011 |      |  |    |        |

**Normal and branched chain alkanes, >=C7**

|       |      |                   |  |  |
|-------|------|-------------------|--|--|
| List  | EH40 |                   |  |  |
| Value | 1200 | mg/m <sup>3</sup> |  |  |

**Cycloalkanes, >=C7**

|                           |      |                   |     |        |
|---------------------------|------|-------------------|-----|--------|
| List                      | EH40 |                   |     |        |
| Value                     | 800  | mg/m <sup>3</sup> |     |        |
| List                      | HTP  |                   |     |        |
| Value                     |      |                   | 900 | ppm(V) |
| Short term exposure limit |      | 1200              |     |        |
| Maximum limit value: ppm  |      |                   |     |        |

**Derived No/Minimal Effect Levels (DNEL/DMEL) \*\*\*****2-Butoxyethyl acetate**

|                     |                                |  |  |       |
|---------------------|--------------------------------|--|--|-------|
| Reference substance | 2-Butoxyethyl acetate          |  |  |       |
| Type of value       | Derived No Effect Level (DNEL) |  |  |       |
| Reference group     | Worker                         |  |  |       |
| Route of exposure   | dermal                         |  |  |       |
| Mode of action      | Acute effects                  |  |  |       |
| Concentration       | 102                            |  |  | mg/kg |
| Source              | Literature value               |  |  |       |

|                   |                                |  |  |       |
|-------------------|--------------------------------|--|--|-------|
| Type of value     | 2-Butoxyethyl acetate          |  |  |       |
|                   | Derived No Effect Level (DNEL) |  |  |       |
| Reference group   | Worker                         |  |  |       |
| Route of exposure | inhalative                     |  |  |       |
| Mode of action    | Acute effects                  |  |  |       |
| Concentration     | 775                            |  |  | mg/kg |
| Source            | Literature value               |  |  |       |

|                   |                                |  |  |       |
|-------------------|--------------------------------|--|--|-------|
| Type of value     | 2-Butoxyethyl acetate          |  |  |       |
|                   | Derived No Effect Level (DNEL) |  |  |       |
| Reference group   | Consumer                       |  |  |       |
| Route of exposure | dermal                         |  |  |       |
| Mode of action    | Acute effects                  |  |  |       |
| Concentration     | 27                             |  |  | mg/kg |
| Source            | Literature value               |  |  |       |

|                   |                                |  |  |       |
|-------------------|--------------------------------|--|--|-------|
| Type of value     | 2-Butoxyethyl acetate          |  |  |       |
|                   | Derived No Effect Level (DNEL) |  |  |       |
| Reference group   | Consumer                       |  |  |       |
| Route of exposure | inhalative                     |  |  |       |
| Concentration     | 499                            |  |  | mg/kg |
| Source            | Literature value               |  |  |       |

Safety data sheet in accordance with regulation (EC) No 1907/2006



Trade name: Marabu-GlasArt 400, 50 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130205400

Replaces Version: 6 / GB

Print date: 10.03.16

Type of value 2-Butoxyethyl acetate  
 Derived No Effect Level (DNEL)  
 Reference group Consumer  
 Route of exposure oral  
 Mode of action Acute effects  
 Concentration 18 mg/kg  
 Source Literature value

Type of value 2-Butoxyethyl acetate  
 Derived No Effect Level (DNEL)  
 Reference group Consumer  
 Route of exposure inhalative  
 Mode of action Local effects  
 Concentration 166 mg/kg  
 Source Literature value

Type of value 2-Butoxyethyl acetate  
 Derived No Effect Level (DNEL)  
 Reference group Consumer  
 Route of exposure dermal  
 Mode of action Chronic effects  
 Concentration 36 mg/kg  
 Source Literature value

Type of value 2-Butoxyethyl acetate  
 Derived No Effect Level (DNEL)  
 Reference group Consumer  
 Route of exposure inhalative  
 Mode of action Chronic effects  
 Concentration 67 mg/kg  
 Source Literature value

Type of value 2-Butoxyethyl acetate  
 Derived No Effect Level (DNEL)  
 Reference group Consumer  
 Route of exposure oral  
 Mode of action Chronic effects  
 Concentration 4,3 mg/kg  
 Source Literature value

Type of value 2-Butoxyethyl acetate  
 Derived No Effect Level (DNEL)  
 Reference group Worker  
 Route of exposure dermal  
 Mode of action Chronic effects  
 Concentration 102 mg/kg  
 Source Literature value

Type of value 2-Butoxyethyl acetate  
 Derived No Effect Level (DNEL)  
 Reference group Worker  
 Route of exposure inhalative  
 Mode of action Chronic effects  
 Concentration 133 mg/kg  
 Source Literature value



Trade name: Marabu-GlasArt 400, 50 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130205400

Replaces Version: 6 / GB

Print date: 10.03.16

**1-Methoxy-2-propanol**

|                      |                                |                   |
|----------------------|--------------------------------|-------------------|
| Type of value        | Derived No Effect Level (DNEL) |                   |
| Reference group      | Worker                         |                   |
| Duration of exposure | Acute                          |                   |
| Route of exposure    | inhalative                     |                   |
| Mode of action       | Local effects                  |                   |
| Concentration        | 553,5                          | mg/m <sup>3</sup> |

|                      |                                |                 |
|----------------------|--------------------------------|-----------------|
| Type of value        | Derived No Effect Level (DNEL) |                 |
| Reference group      | Worker                         |                 |
| Duration of exposure | Long term                      |                 |
| Route of exposure    | dermal                         |                 |
| Mode of action       | Systemic effects               |                 |
| Concentration        | 50,6                           | mg/person/<br>d |

|                      |                                |                   |
|----------------------|--------------------------------|-------------------|
| Type of value        | Derived No Effect Level (DNEL) |                   |
| Reference group      | Worker                         |                   |
| Duration of exposure | Long term                      |                   |
| Route of exposure    | inhalative                     |                   |
| Mode of action       | Systemic effects               |                   |
| Concentration        | 369                            | mg/m <sup>3</sup> |

|                      |                                |       |
|----------------------|--------------------------------|-------|
| Type of value        | Derived No Effect Level (DNEL) |       |
| Reference group      | General Population             |       |
| Duration of exposure | Long term                      |       |
| Route of exposure    | dermal                         |       |
| Mode of action       | Systemic effects               |       |
| Concentration        | 18,1                           | mg/kg |

|                      |                                |                   |
|----------------------|--------------------------------|-------------------|
| Type of value        | Derived No Effect Level (DNEL) |                   |
| Reference group      | General Population             |                   |
| Duration of exposure | Long term                      |                   |
| Route of exposure    | inhalative                     |                   |
| Mode of action       | Systemic effects               |                   |
| Concentration        | 43,9                           | mg/m <sup>3</sup> |

|                      |                                |         |
|----------------------|--------------------------------|---------|
| Type of value        | Derived No Effect Level (DNEL) |         |
| Reference group      | General Population             |         |
| Duration of exposure | Long term                      |         |
| Route of exposure    | oral                           |         |
| Mode of action       | Systemic effects               |         |
| Concentration        | 3,3                            | mg/kg/d |

**Naphtha (petroleum), hydrotreated heavy**

|                      |                                |       |
|----------------------|--------------------------------|-------|
| Type of value        | Derived No Effect Level (DNEL) |       |
| Reference group      | Worker                         |       |
| Duration of exposure | Long term                      |       |
| Route of exposure    | dermal                         |       |
| Mode of action       | Systemic effects               |       |
| Concentration        | 300                            | mg/kg |

|                      |                                |  |
|----------------------|--------------------------------|--|
| Type of value        | Derived No Effect Level (DNEL) |  |
| Reference group      | Consumer                       |  |
| Duration of exposure | Long term                      |  |
| Route of exposure    | oral                           |  |
| Mode of action       | Systemic effects               |  |

Safety data sheet in accordance with regulation (EC) No 1907/2006



Trade name: Marabu-GlasArt 400, 50 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130205400

Replaces Version: 6 / GB

Print date: 10.03.16

Concentration 300 mg/kg

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Duration of exposure Long term

Route of exposure dermal

Mode of action Systemic effects

Concentration 300 mg/kg

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Duration of exposure Long term

Route of exposure inhalative

Mode of action Systemic effects

Concentration 900 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)

Reference group Worker

Duration of exposure Long term

Route of exposure inhalative

Mode of action Systemic effects

Concentration 1500 mg/m<sup>3</sup>

**Predicted No Effect Concentration (PNEC)**

**2-Butoxyethyl acetate**

Reference substance 2-Butoxyethyl acetate

Type of value PNEC

Type Water

Concentration 0,304 mg/l

Source Literature value

Type of value 2-Butoxyethyl acetate

Type PNEC

Type Aquatic

Concentration 0,0304 g/l

Source Literature value

Type of value 2-Butoxyethyl acetate

Type PNEC

Type Sediment

Concentration 2,03 mg/kg

Source Literature value

Type of value 2-Butoxyethyl acetate

Type PNEC

Type Marine sediment

Concentration 0,203 mg/kg

Source Literature value

Type of value 2-Butoxyethyl acetate

Type PNEC

Type Soil

Concentration 0,68 mg/kg

Source Literature value

**1-Methoxy-2-propanol**

Type of value PNEC





Trade name: Marabu-GlasArt 400, 50 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130205400

Replaces Version: 6 / GB

Print date: 10.03.16

|               |                              |       |
|---------------|------------------------------|-------|
| Type          | Freshwater                   |       |
| Concentration | 10                           | mg/l  |
| Type of value | PNEC                         |       |
| Type          | Water                        |       |
| Concentration | 41,6                         | mg/kg |
| Type of value | PNEC                         |       |
| Type          | Sediment                     |       |
| Concentration | 41,6                         | mg/kg |
| Type of value | PNEC                         |       |
| Type          | Marine sediment              |       |
| Concentration | 4,17                         | mg/kg |
| Type of value | PNEC                         |       |
| Type          | Soil                         |       |
| Concentration | 2,47                         | mg/kg |
| Type of value | PNEC                         |       |
| Type          | Sewage treatment plant (STP) |       |
| Concentration | 100                          | mg/l  |

## 8.2. Exposure controls

### Exposure controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

### Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. Full mask, filter A

### Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

For prolonged or repeated handling nitrile rubber gloves with textile undergloves are required.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

### Eye protection

Use safety eyewear designed to protect against splash of liquids.

### Body protection

Cotton or cotton/synthetic overalls or coveralls are normally suitable.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|        |            |
|--------|------------|
| Form   | Liquid     |
| Colour | colourless |



Trade name: Marabu-GlasArt 400, 50 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130205400

Replaces Version: 6 / GB

Print date: 10.03.16

|                                                     |                     |       |                   |
|-----------------------------------------------------|---------------------|-------|-------------------|
| <b>Odour</b>                                        | solvent-like        |       |                   |
| <b>Odour threshold</b>                              |                     |       |                   |
| Remarks                                             | No data available   |       |                   |
| <b>pH value</b>                                     |                     |       |                   |
| Remarks                                             | Not applicable      |       |                   |
| <b>Melting point</b>                                |                     |       |                   |
| Remarks                                             | not determined      |       |                   |
| <b>Freezing point</b>                               |                     |       |                   |
| Remarks                                             | not determined      |       |                   |
| <b>Initial boiling point and boiling range</b>      |                     |       |                   |
| Value                                               | appr. 120           |       | °C                |
| Pressure                                            | 1.013               | hPa   |                   |
| Source                                              | Literature value    |       |                   |
| <b>Flash point</b>                                  |                     |       |                   |
| Value                                               | 48                  |       | °C                |
| Method                                              | ASTM D 6450 (CCCFP) |       |                   |
| <b>Evaporation rate (ether = 1) :</b>               |                     |       |                   |
| Remarks                                             | not determined      |       |                   |
| <b>Flammability (solid, gas)</b>                    |                     |       |                   |
| Remarks                                             | Not applicable      |       |                   |
| <b>Upper/lower flammability or explosive limits</b> |                     |       |                   |
| Lower explosion limit                               | appr. 0,7           |       | %(V)              |
| Upper explosion limit                               | appr. 13,7          |       | %(V)              |
| Source                                              | Literature value    |       |                   |
| <b>Vapour pressure</b>                              |                     |       |                   |
| Value                                               | appr. 8             |       | hPa               |
| Temperature                                         | 20                  | °C    |                   |
| Method                                              | calculated          |       |                   |
| <b>Vapour density</b>                               |                     |       |                   |
| Remarks                                             | not determined      |       |                   |
| <b>Density</b>                                      |                     |       |                   |
| Value                                               | 0,91                |       | g/cm <sup>3</sup> |
| Temperature                                         | 20                  | °C    |                   |
| Method                                              | DIN EN ISO 2811     |       |                   |
| <b>Solubility in water</b>                          |                     |       |                   |
| Remarks                                             | partially miscible  |       |                   |
| <b>Partition coefficient: n-octanol/water</b>       |                     |       |                   |
| Remarks                                             | Not applicable      |       |                   |
| <b>Ignition temperature</b>                         |                     |       |                   |
| Value                                               | appr. 200           |       | °C                |
| Source                                              | Literature value    |       |                   |
| <b>Efflux time</b>                                  |                     |       |                   |
| Value                                               | < 40                | to 75 | s                 |
| Temperature                                         | 20                  | °C    |                   |
| Method                                              | DIN 53211 4 mm      |       |                   |
| <b>Explosive properties</b>                         |                     |       |                   |
| evaluation                                          | no                  |       |                   |
| <b>Oxidising properties</b>                         |                     |       |                   |



Trade name: Marabu-GlasArt 400, 50 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130205400

Replaces Version: 6 / GB

Print date: 10.03.16

evaluation

None known

**9.2. Other information****Other information**

The physical specifications are approximate values and refer to the used safety relevant component(s).

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No hazardous reactions when stored and handled according to prescribed instructions.

**10.2. Chemical stability**

Stable under recommended storage and handling conditions (see section 7).

**10.3. Possibility of hazardous reactions**

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

**10.4. Conditions to avoid**

When exposed to high temperatures may produce hazardous decomposition products.

**10.5. Incompatible materials**

No hazardous reactions when stored and handled according to prescribed instructions.

**10.6. Hazardous decomposition products**

See chapter 5.2 (Firefighting measures - Special hazards arising from the substance or mixture).

**SECTION 11: Toxicological information****11.1. Information on toxicological effects****Acute oral toxicity**

|        |   |                                                  |       |
|--------|---|--------------------------------------------------|-------|
| ATE    | > | 2.000                                            | mg/kg |
| Method |   | calculated value (Regulation (EC) No. 1272/2008) |       |

**Acute oral toxicity (Components)****1-Methoxy-2-propanol**

|         |     |      |       |
|---------|-----|------|-------|
| Species | rat |      |       |
| LD50    |     | 5200 | mg/kg |

**Acute dermal toxicity**

|        |   |                                                  |       |
|--------|---|--------------------------------------------------|-------|
| ATE    | > | 2.000                                            | mg/kg |
| Method |   | calculated value (Regulation (EC) No. 1272/2008) |       |

**Acute dermal toxicity (Components)****1-Methoxy-2-propanol**

|         |        |       |       |
|---------|--------|-------|-------|
| Species | rabbit |       |       |
| LD50    |        | 14000 | mg/kg |

**Acute inhalational toxicity**

|                     |   |                                                  |      |
|---------------------|---|--------------------------------------------------|------|
| ATE                 | > | 20                                               | mg/l |
| Administration/Form |   | Vapors                                           |      |
| Method              |   | calculated value (Regulation (EC) No. 1272/2008) |      |

|     |   |   |      |
|-----|---|---|------|
| ATE | > | 5 | mg/l |
|-----|---|---|------|

|                     |  |                                                  |  |
|---------------------|--|--------------------------------------------------|--|
| Administration/Form |  | Dust/Mist                                        |  |
| Method              |  | calculated value (Regulation (EC) No. 1272/2008) |  |

**Aspiration hazard**

No special hazards have to be mentioned.

**Experience in practice**



Trade name: Marabu-GlasArt 400, 50 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130205400

Replaces Version: 6 / GB

Print date: 10.03.16

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

### Other information

There are no data available on the mixture itself.

The mixture has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly.

## SECTION 12: Ecological information

### 12.1. Toxicity

#### General information

There are no data available on the mixture itself. Do not allow to enter drains or water courses. The mixture has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is not classified as dangerous for the environment.

#### Fish toxicity (Components)

##### 1-Methoxy-2-propanol

|                      |                                       |      |      |
|----------------------|---------------------------------------|------|------|
| Species              | golden orfe ( <i>Leuciscus idus</i> ) |      |      |
| LC0                  | >                                     | 4600 | mg/l |
| Duration of exposure | 96                                    | h    |      |

#### Daphnia toxicity (Components)

##### 1-Methoxy-2-propanol

|                      |               |       |      |
|----------------------|---------------|-------|------|
| Species              | Daphnia magna |       |      |
| EC50                 |               | 23300 | mg/l |
| Duration of exposure | 48            | h     |      |

#### Algae toxicity (Components)

##### 1-Methoxy-2-propanol

|                      |             |      |      |
|----------------------|-------------|------|------|
| Species              | Desmodesmus |      |      |
| EC50                 | >           | 1000 | mg/l |
| Duration of exposure | 168         | h    |      |

#### Bacteria toxicity (Components)

##### 1-Methoxy-2-propanol

|         |                  |      |      |
|---------|------------------|------|------|
| Species | activated sludge |      |      |
| EC50    | >                | 1000 | mg/l |

### 12.2. Persistence and degradability

#### General information

No data available

#### Biodegradability (Components)

##### 1-Methoxy-2-propanol

|                             |                                                                  |   |
|-----------------------------|------------------------------------------------------------------|---|
| Value                       | 90                                                               | % |
| Duration of test evaluation | 28                                                               | d |
| Method                      | Readily biodegradable (according to OECD criteria)<br>OECD 301 F |   |

### 12.3. Bioaccumulative potential



Trade name: Marabu-GlasArt 400, 50 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130205400

Replaces Version: 6 / GB

Print date: 10.03.16

**General information**

There are no data available on the mixture itself.

**Partition coefficient: n-octanol/water**

Remarks Not applicable

**12.4. Mobility in soil**

**General information**

There are no data available on the mixture itself.

**12.5. Results of PBT and vPvB assessment**

**General information**

There are no data available on the mixture itself.

**12.6. Other adverse effects**

**General information**

There are no data available on the mixture itself.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Disposal recommendations for the product**

Do not allow to enter drains or water courses.

Wastes and emptied containers should be classified in accordance with relevant national regulation.

The European Waste Catalogue classification of this product, when disposed of as waste is

EWC waste code 08 01 11\* waste paint and varnish containing organic solvents or other dangerous substances

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

For further information contact your local waste authority.

**Disposal recommendations for packaging**

Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers.

Empty containers must be scrapped or reconditioned.

Not emptied containers are hazardous waste (waste code number 150110).

**SECTION 14: Transport information**

**Land transport ADR/RID**

**14.1. UN number**

UN 1263

**14.2. UN proper shipping name**

PAINT

**14.3. Transport hazard class(es)**

Class 3

Label 3

**14.4. Packing group**

Packing group III

Special provision 640E

Limited Quantity 5 I

Transport category 4

**14.5. Environmental hazards**

-

Tunnel restriction code D/E

**Marine transport IMDG/GGVSee**



Trade name: Marabu-GlasArt 400, 50 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130205400

Replaces Version: 6 / GB

Print date: 10.03.16

**14.1. UN number**

UN 1263

**14.2. UN proper shipping name**

PAINT

**14.3. Transport hazard class(es)**

Class 3

**14.4. Packing group**

Packing group III

**14.5. Environmental hazards**

no

**Air transport ICAO/IATA**

**14.1. UN number**

UN 1263

**14.2. UN proper shipping name**

PAINT

**14.3. Transport hazard class(es)**

Class 3

**14.4. Packing group**

Packing group III

**14.5. Environmental hazards**

-

**Information for all modes of transport**

**14.6. Special precautions for user**

Transport within the user's premises:

Always transport in closed containers that are upright and secure.

Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Other information**

**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

no

**SECTION 15: Regulatory information \*\*\***

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Major-accident categories acc. 96/82/EC**

|          |   |           |           |    |            |    |
|----------|---|-----------|-----------|----|------------|----|
| Category | 6 | Flammable | 5.000.000 | kg | 50.000.000 | kg |
|----------|---|-----------|-----------|----|------------|----|

**VOC \*\*\***

|          |      |   |       |     |
|----------|------|---|-------|-----|
| VOC (EU) | 33,2 | % | 302,2 | g/l |
|----------|------|---|-------|-----|

**Other information**

The product does not contain substances of very high concern (SVHC).

**Other information**

All components are contained in the TSCA inventory or exempted.

All components are contained in the AICS inventory.

All components are contained in the PICCS inventory.

All components are contained in the DSL inventory.

All components are contained in the ENCS inventory.

**15.2. Chemical safety assessment**

For this preparation a chemical safety assessment has not been carried out.

**SECTION 16: Other information**

**Hazard statements listed in Chapter 3**



Trade name: Marabu-GlasArt 400, 50 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130205400

Replaces Version: 6 / GB

Print date: 10.03.16

|        |                                                       |
|--------|-------------------------------------------------------|
| EUH066 | Repeated exposure may cause skin dryness or cracking. |
| H226   | Flammable liquid and vapour.                          |
| H302   | Harmful if swallowed.                                 |
| H304   | May be fatal if swallowed and enters airways.         |
| H312   | Harmful in contact with skin.                         |
| H319   | Causes serious eye irritation.                        |
| H332   | Harmful if inhaled.                                   |
| H336   | May cause drowsiness or dizziness.                    |
| H361d  | Suspected of damaging the unborn child.               |
| H412   | Harmful to aquatic life with long lasting effects.    |

**CLP categories listed in Chapter 3**

|                   |                                                              |
|-------------------|--------------------------------------------------------------|
| Acute Tox. 4      | Acute toxicity, Category 4                                   |
| Aquatic Chronic 3 | Hazardous to the aquatic environment, chronic, Category 3    |
| Asp. Tox. 1       | Aspiration hazard, Category 1                                |
| Eye Irrit. 2      | Eye irritation, Category 2                                   |
| Flam. Liq. 3      | Flammable liquid, Category 3                                 |
| Repr. 2           | Reproductive toxicity, Category 2                            |
| STOT SE 3         | Specific target organ toxicity - single exposure, Category 3 |

**Supplemental information**

Relevant changes compared with the previous version of the safety data sheet are marked with: \*\*\*  
 This information is based on our present state of knowledge. However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship.  
 The information in this Safety Data Sheet is based on the present state of knowledge and current legislation.

It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions.

As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.