



Trade name: Marabu-GlasArt 463, 50 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130205463

Replaces Version: 6 / GB

Print date: 10.03.16

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Marabu-GlasArt 463, 50 ml

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/preparation

Paint

1.3. Details of the supplier of the safety data sheet

Address

Marabu GmbH & Co. KG
Asperger Strasse 4
71732 Tamm
Germany
Telephone no. +49-7141/691-0
Fax no. +49-7141/691-147
Information provided by / telephone Department product safety
E-mail address of person responsible PRSI@marabu.de
for this SDS

1.4. Emergency telephone number

(+49) (0)621-60-43333

SECTION 2: Hazards identification ***

2.1. Classification of the substance or mixture

Classification (Regulation (EC) No. 1272/2008)

Classification (Regulation (EC) No. 1272/2008)
Flam. Liq. 3 H226
STOT SE 3 H336

2.2. Label elements

Labelling according to regulation (EC) No 1272/2008

Hazard pictograms



Signal word

Warning

Hazard statements ***

H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition



Trade name: Marabu-GlasArt 463, 50 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130205463

Replaces Version: 6 / GB

Print date: 10.03.16

P271 sources. No smoking.
 P405 Use only outdoors or in a well-ventilated area.
 P501.9 Store locked up.
 Dispose of contents/container as problematic waste.

Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)

contains *** 1-Methoxy-2-propanol;Naphtha (petroleum), hydrotreated heavy

2.3. Other hazards

No special hazards have to be mentioned.

SECTION 3: Composition/information on ingredients ***

3.2. Mixtures

Chemical characterization

Paint based on alkyd resins and on solvents

Hazardous ingredients ***

1-Methoxy-2-propanol

CAS No. 107-98-2
 EINECS no. 203-539-1
 Registration no. 01-2119457435-35
 Concentration >= 25 < 50 %

Classification (Regulation (EC) No. 1272/2008)
 STOT SE 3 H336
 Flam. Liq. 3 H226

Naphtha (petroleum), hydrotreated heavy

CAS No. 64742-48-9
 EINECS no. 919-857-5
 Registration no. 01-2119463258-33
 Concentration >= 10 < 20 %

Classification (Regulation (EC) No. 1272/2008)
 Asp. Tox. 1 H304
 Flam. Liq. 3 H226
 STOT SE 3 H336
 EUH066

2-Butoxyethyl acetate

CAS No. 112-07-2
 EINECS no. 203-933-3
 Registration no. 01-2119475112-47
 Concentration >= 1 < 10 %

Classification (Regulation (EC) No. 1272/2008)
 Acute Tox. 4 H332
 Acute Tox. 4 H312
 Acute Tox. 4 H302

C.I.Solvent Yellow 79 (-)

CAS No. 85455-32-9
 EINECS no. 287-267-9
 Concentration >= 1 < 10 %

Classification (Regulation (EC) No. 1272/2008)



Trade name: Marabu-GlasArt 463, 50 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130205463

Replaces Version: 6 / GB

Print date: 10.03.16

| | |
|-------------------|------|
| Eye Irrit. 2 | H319 |
| Aquatic Chronic 3 | H412 |

C.I.Solvent Blue 70

| | |
|---------------|-------------|
| CAS No. | 94277-77-7 |
| EINECS no. | 304-661-9 |
| Concentration | >= 1 < 10 % |

| | |
|--|------|
| Classification (Regulation (EC) No. 1272/2008) | |
| Aquatic Chronic 3 | H412 |

Hexanoic acid, 2-ethyl-, zinc salt, basic

| | |
|------------------|------------------|
| CAS No. | 85203-81-2 |
| EINECS no. | 286-272-3 |
| Registration no. | 01-2119979093-30 |
| Concentration | >= 0,1 < 1 % |

| | |
|--|-------|
| Classification (Regulation (EC) No. 1272/2008) | |
| Eye Irrit. 2 | H319 |
| Repr. 2 | H361d |
| Aquatic Chronic 3 | H412 |

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Until now no symptoms known so far.

4.3. Indication of any immediate medical attention and special treatment needed**Hints for the physician / treatment**

Treat symptomatically

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Recommended: alcohol resistant foam, CO₂, powders, water spray/mist, Not be used for safety reasons:



Trade name: Marabu-GlasArt 463, 50 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130205463

Replaces Version: 6 / GB

Print date: 10.03.16

water jet

5.2. Special hazards arising from the substance or mixture

In the event of fire the following can be released: Carbon monoxide (CO); Carbon dioxide (CO₂); dense black smoke; Nitrogen oxides (NO_x)

5.3. Advice for firefighters

Special protective equipment for fire-fighting

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Refer to protective measures listed in Sections 7 and 8.

6.2. Environmental precautions

Do not allow to enter drains or waterways. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

6.4. Reference to other sections

Information regarding Safe handling, see Section 7. Information regarding personal protective measures, see Section 8. Information regarding waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Avoid skin and eye contact. Avoid the inhalation of particulates and spray mist arising from the application of this mixture. Smoking, eating and drinking shall be prohibited in application area. For personal protection see Section 8. Never use pressure to empty: container is not a pressure vessel. Always keep in containers of same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or water courses.

Advice on protection against fire and explosion

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

Classification of fires / temperature class / Ignition group / Dust explosion class

| | |
|-------------------------|-----------------------------------|
| Classification of fires | B (Combustible liquid substances) |
| Temperature class | T4 |

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Electrical installations/working materials must comply with the local applied technological safety standards. Storage rooms in which filling operations take place must have a conducting floor. Store in



Trade name: Marabu-GlasArt 463, 50 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130205463

Replaces Version: 6 / GB

Print date: 10.03.16

accordance with national regulation

Hints on storage assembly

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

Further information on storage conditions

Observe label precautions. Store between 15 and 30 °C in a dry, well ventilated place away from sources of heat and direct sunlight. Keep container tightly closed. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

7.3. Specific end use(s)

Paint

SECTION 8: Exposure controls/personal protection ***

8.1. Control parameters

Exposure limit values ***

1-Methoxy-2-propanol

| | | | | |
|---|------|-------------------|-----|--------|
| List | EH40 | | | |
| Type | WEL | | | |
| Value | 375 | mg/m ³ | 100 | ppm(V) |
| Short term exposure limit | 560 | mg/m ³ | 150 | ppm(V) |
| Skin resorption / sensibilisation: Sk; Status: 2011 | | | | |

2-Butoxyethyl acetate

| | | | | |
|---|------|--|----|--------|
| List | EH40 | | | |
| Type | WEL | | | |
| Value | 133 | | 20 | ppm(V) |
| Short term exposure limit | 332 | | 50 | ppm(V) |
| Skin resorption / sensibilisation: Sk; Status: 2011 | | | | |

Normal and branched chain alkanes, >=C7

| | | | | |
|-------|------|-------------------|--|--|
| List | EH40 | | | |
| Value | 1200 | mg/m ³ | | |

Cycloalkanes, >=C7

| | | | | |
|---------------------------|------|-------------------|------|--------|
| List | EH40 | | | |
| Value | 800 | mg/m ³ | | |
| List | HTP | | | |
| Value | | | 900 | ppm(V) |
| Short term exposure limit | | | 1200 | |
| Maximum limit value: ppm | | | | |

Derived No/Minimal Effect Levels (DNEL/DMEL) ***

2-Butoxyethyl acetate

| | | | | |
|---------------------|--------------------------------|--|--|-------|
| Reference substance | 2-Butoxyethyl acetate | | | |
| Type of value | Derived No Effect Level (DNEL) | | | |
| Reference group | Worker | | | |
| Route of exposure | dermal | | | |
| Mode of action | Acute effects | | | |
| Concentration | 102 | | | mg/kg |
| Source | Literature value | | | |

| | | | | |
|-------------------|--------------------------------|--|--|-------|
| Type of value | 2-Butoxyethyl acetate | | | |
| | Derived No Effect Level (DNEL) | | | |
| Reference group | Worker | | | |
| Route of exposure | inhalative | | | |
| Mode of action | Acute effects | | | |
| Concentration | 775 | | | mg/kg |

Safety data sheet in accordance with regulation (EC) No 1907/2006



Trade name: Marabu-GlasArt 463, 50 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130205463

Replaces Version: 6 / GB

Print date: 10.03.16

| | | |
|-------------------|--------------------------------|-------|
| Source | Literature value | |
| Type of value | 2-Butoxyethyl acetate | |
| Reference group | Derived No Effect Level (DNEL) | |
| Route of exposure | Consumer | |
| Mode of action | dermal | |
| Concentration | Acute effects | |
| Source | 27 | mg/kg |
| Type of value | Literature value | |
| Reference group | 2-Butoxyethyl acetate | |
| Route of exposure | Derived No Effect Level (DNEL) | |
| Mode of action | Consumer | |
| Concentration | inhalative | |
| Source | 499 | mg/kg |
| Type of value | Literature value | |
| Reference group | 2-Butoxyethyl acetate | |
| Route of exposure | Derived No Effect Level (DNEL) | |
| Mode of action | Consumer | |
| Concentration | oral | |
| Source | Acute effects | |
| Type of value | 18 | mg/kg |
| Reference group | Literature value | |
| Route of exposure | 2-Butoxyethyl acetate | |
| Mode of action | Derived No Effect Level (DNEL) | |
| Concentration | Consumer | |
| Source | inhalative | |
| Type of value | Local effects | |
| Reference group | 166 | mg/kg |
| Route of exposure | Literature value | |
| Mode of action | 2-Butoxyethyl acetate | |
| Concentration | Derived No Effect Level (DNEL) | |
| Source | Consumer | |
| Type of value | dermal | |
| Reference group | Chronic effects | |
| Route of exposure | 36 | mg/kg |
| Mode of action | Literature value | |
| Concentration | 2-Butoxyethyl acetate | |
| Source | Derived No Effect Level (DNEL) | |
| Type of value | Consumer | |
| Reference group | inhalative | |
| Route of exposure | Chronic effects | |
| Mode of action | 67 | mg/kg |
| Concentration | Literature value | |
| Source | 2-Butoxyethyl acetate | |
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Consumer | |
| Route of exposure | oral | |
| Mode of action | Chronic effects | |
| Concentration | 4,3 | mg/kg |
| Source | Literature value | |
| Type of value | 2-Butoxyethyl acetate | |

Safety data sheet in accordance with regulation (EC) No 1907/2006



Trade name: Marabu-GlasArt 463, 50 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130205463

Replaces Version: 6 / GB

Print date: 10.03.16

| | | |
|-------------------|--------------------------------|-------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Worker | |
| Route of exposure | dermal | |
| Mode of action | Chronic effects | |
| Concentration | 102 | mg/kg |
| Source | Literature value | |

| | | |
|-------------------|--------------------------------|-------|
| | 2-Butoxyethyl acetate | |
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Worker | |
| Route of exposure | inhalative | |
| Mode of action | Chronic effects | |
| Concentration | 133 | mg/kg |
| Source | Literature value | |

1-Methoxy-2-propanol

| | | |
|----------------------|--------------------------------|-------------------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Worker | |
| Duration of exposure | Acute | |
| Route of exposure | inhalative | |
| Mode of action | Local effects | |
| Concentration | 553,5 | mg/m ³ |

| | | |
|----------------------|--------------------------------|-----------------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Worker | |
| Duration of exposure | Long term | |
| Route of exposure | dermal | |
| Mode of action | Systemic effects | |
| Concentration | 50,6 | mg/person/ d |

| | | |
|----------------------|--------------------------------|-------------------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Worker | |
| Duration of exposure | Long term | |
| Route of exposure | inhalative | |
| Mode of action | Systemic effects | |
| Concentration | 369 | mg/m ³ |

| | | |
|----------------------|--------------------------------|-------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | General Population | |
| Duration of exposure | Long term | |
| Route of exposure | dermal | |
| Mode of action | Systemic effects | |
| Concentration | 18,1 | mg/kg |

| | | |
|----------------------|--------------------------------|-------------------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | General Population | |
| Duration of exposure | Long term | |
| Route of exposure | inhalative | |
| Mode of action | Systemic effects | |
| Concentration | 43,9 | mg/m ³ |

| | | |
|----------------------|--------------------------------|--|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | General Population | |
| Duration of exposure | Long term | |
| Route of exposure | oral | |
| Mode of action | Systemic effects | |



Trade name: Marabu-GlasArt 463, 50 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130205463

Replaces Version: 6 / GB

Print date: 10.03.16

Concentration 3,3 mg/kg/d

Naphtha (petroleum), hydrotreated heavy

Type of value Derived No Effect Level (DNEL)
 Reference group Worker
 Duration of exposure Long term
 Route of exposure dermal
 Mode of action Systemic effects
 Concentration 300 mg/kg

Type of value Derived No Effect Level (DNEL)
 Reference group Consumer
 Duration of exposure Long term
 Route of exposure oral
 Mode of action Systemic effects
 Concentration 300 mg/kg

Type of value Derived No Effect Level (DNEL)
 Reference group Consumer
 Duration of exposure Long term
 Route of exposure dermal
 Mode of action Systemic effects
 Concentration 300 mg/kg

Type of value Derived No Effect Level (DNEL)
 Reference group Consumer
 Duration of exposure Long term
 Route of exposure inhalative
 Mode of action Systemic effects
 Concentration 900 mg/m³

Type of value Derived No Effect Level (DNEL)
 Reference group Worker
 Duration of exposure Long term
 Route of exposure inhalative
 Mode of action Systemic effects
 Concentration 1500 mg/m³

Predicted No Effect Concentration (PNEC)

2-Butoxyethyl acetate

Reference substance 2-Butoxyethyl acetate
 Type of value PNEC
 Type Water
 Concentration 0,304 mg/l
 Source Literature value

Type of value 2-Butoxyethyl acetate
 PNEC
 Type Aquatic
 Concentration 0,0304 g/l
 Source Literature value

Type of value 2-Butoxyethyl acetate
 PNEC
 Type Sediment
 Concentration 2,03 mg/kg
 Source Literature value



Trade name: Marabu-GlasArt 463, 50 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130205463

Replaces Version: 6 / GB

Print date: 10.03.16

| | | |
|---------------|-----------------------|-------|
| Type of value | 2-Butoxyethyl acetate | |
| Type | PNEC | |
| Concentration | Marine sediment | |
| Source | 0,203 | mg/kg |
| | Literature value | |

| | | |
|---------------|-----------------------|-------|
| Type of value | 2-Butoxyethyl acetate | |
| Type | PNEC | |
| Concentration | Soil | |
| Source | 0,68 | mg/kg |
| | Literature value | |

1-Methoxy-2-propanol

| | | |
|---------------|------------|------|
| Type of value | PNEC | |
| Type | Freshwater | |
| Concentration | 10 | mg/l |

| | | |
|---------------|-------|-------|
| Type of value | PNEC | |
| Type | Water | |
| Concentration | 41,6 | mg/kg |

| | | |
|---------------|----------|-------|
| Type of value | PNEC | |
| Type | Sediment | |
| Concentration | 41,6 | mg/kg |

| | | |
|---------------|-----------------|-------|
| Type of value | PNEC | |
| Type | Marine sediment | |
| Concentration | 4,17 | mg/kg |

| | | |
|---------------|------|-------|
| Type of value | PNEC | |
| Type | Soil | |
| Concentration | 2,47 | mg/kg |

| | | |
|---------------|------------------------------|------|
| Type of value | PNEC | |
| Type | Sewage treatment plant (STP) | |
| Concentration | 100 | mg/l |

8.2. Exposure controls

Exposure controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. Full mask, filter A

Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.
 For prolonged or repeated handling nitrile rubber gloves with textile undergloves are required. The breakthrough time must be greater than the end use time of the product.
 The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.
 Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly.



Trade name: Marabu-GlasArt 463, 50 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130205463

Replaces Version: 6 / GB

Print date: 10.03.16

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

Eye protection

Use safety eyewear designed to protect against splash of liquids.

Body protection

Cotton or cotton/synthetic overalls or coveralls are normally suitable.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

| | | | |
|---|---------------------|-----|-------------------|
| Form | Liquid | | |
| Colour | coloured | | |
| Odour | solvent-like | | |
| Odour threshold | | | |
| Remarks | No data available | | |
| pH value | | | |
| Remarks | Not applicable | | |
| Melting point | | | |
| Remarks | not determined | | |
| Freezing point | | | |
| Remarks | not determined | | |
| Initial boiling point and boiling range | | | |
| Value | appr. 120 | | °C |
| Pressure | 1.013 | hPa | |
| Source | Literature value | | |
| Flash point | | | |
| Value | 48 | | °C |
| Method | ASTM D 6450 (CCCFP) | | |
| Evaporation rate (ether = 1) : | | | |
| Remarks | not determined | | |
| Flammability (solid, gas) | | | |
| Not applicable | | | |
| Upper/lower flammability or explosive limits | | | |
| Lower explosion limit | appr. 0,7 | | %(V) |
| Upper explosion limit | appr. 13,7 | | %(V) |
| Source | Literature value | | |
| Vapour pressure | | | |
| Value | appr. 8 | | hPa |
| Temperature | 20 | °C | |
| Method | calculated | | |
| Vapour density | | | |
| Remarks | not determined | | |
| Density | | | |
| Value | 0,93 | | g/cm ³ |
| Temperature | 20 | °C | |
| Method | DIN EN ISO 2811 | | |
| Solubility in water | | | |



Trade name: Marabu-GlasArt 463, 50 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130205463

Replaces Version: 6 / GB

Print date: 10.03.16

Remarks partially miscible

Partition coefficient: n-octanol/water

Remarks Not applicable

Ignition temperature

Value appr. 200 °C

Source Literature value

Efflux time

Value < 40 to 75 s

Temperature 20 °C

Method DIN 53211 4 mm

Explosive properties

evaluation no

Oxidising properties

evaluation None known

9.2. Other information**Other information**

The physical specifications are approximate values and refer to the used safety relevant component(s).

SECTION 10: Stability and reactivity**10.1. Reactivity**

No hazardous reactions when stored and handled according to prescribed instructions.

10.2. Chemical stability

Stable under recommended storage and handling conditions (see section 7).

10.3. Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4. Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition products.

10.5. Incompatible materials

No hazardous reactions when stored and handled according to prescribed instructions.

10.6. Hazardous decomposition products

See chapter 5.2 (Firefighting measures - Special hazards arising from the substance or mixture).

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute oral toxicity**ATE > 2.000 mg/kg
Method calculated value (Regulation (EC) No. 1272/2008)**Acute oral toxicity (Components)****1-Methoxy-2-propanol**Species rat
LD50 5200 mg/kg**Acute dermal toxicity**ATE > 2.000 mg/kg
Method calculated value (Regulation (EC) No. 1272/2008)



Trade name: Marabu-GlasArt 463, 50 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130205463

Replaces Version: 6 / GB

Print date: 10.03.16

Acute dermal toxicity (Components)**1-Methoxy-2-propanol**

| | | | |
|---------|--------|--|-------|
| Species | rabbit | | |
| LD50 | 14000 | | mg/kg |

Acute inhalational toxicity

| | | | |
|---------------------|--|--|------|
| ATE | > 20 | | mg/l |
| Administration/Form | Vapors | | |
| Method | calculated value (Regulation (EC) No. 1272/2008) | | |
| ATE | > 5 | | mg/l |
| Administration/Form | Dust/Mist | | |
| Method | calculated value (Regulation (EC) No. 1272/2008) | | |

Aspiration hazard

No special hazards have to be mentioned.

Experience in practice

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Other information

There are no data available on the mixture itself.

The mixture has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly.

SECTION 12: Ecological information**12.1. Toxicity****General information**

There are no data available on the mixture itself. Do not allow to enter drains or water courses. The mixture has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is not classified as dangerous for the environment, but contains substance(s) dangerous for the environment. See section 3 for details.

Fish toxicity (Components)**1-Methoxy-2-propanol**

| | | | |
|----------------------|---------------------------------------|---|------|
| Species | golden orfe (<i>Leuciscus idus</i>) | | |
| LC0 | > 4600 | | mg/l |
| Duration of exposure | 96 | h | |

Daphnia toxicity (Components)**1-Methoxy-2-propanol**

| | | | |
|----------------------|----------------------|---|------|
| Species | <i>Daphnia magna</i> | | |
| EC50 | 23300 | | mg/l |
| Duration of exposure | 48 | h | |

Algae toxicity (Components)**1-Methoxy-2-propanol**

| | | | |
|----------------------|--------------------|---|------|
| Species | <i>Desmodesmus</i> | | |
| EC50 | > 1000 | | mg/l |
| Duration of exposure | 168 | h | |



Trade name: Marabu-GlasArt 463, 50 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130205463

Replaces Version: 6 / GB

Print date: 10.03.16

Bacteria toxicity (Components)**1-Methoxy-2-propanol**

| | | |
|---------|------------------|------|
| Species | activated sludge | |
| EC50 | > 1000 | mg/l |

12.2. Persistence and degradability**General information**

No data available

Biodegradability (Components)**1-Methoxy-2-propanol**

| | | |
|-----------------------------|--|---|
| Value | 90 | % |
| Duration of test evaluation | 28 | d |
| Method | Readily biodegradable (according to OECD criteria) OECD 301 F | |

12.3. Bioaccumulative potential**General information**

There are no data available on the mixture itself.

Partition coefficient: n-octanol/water

Remarks Not applicable

12.4. Mobility in soil**General information**

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment**General information**

There are no data available on the mixture itself.

12.6. Other adverse effects**General information**

There are no data available on the mixture itself.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations for the product**

Do not allow to enter drains or water courses.

Wastes and emptied containers should be classified in accordance with relevant national regulation.

The European Waste Catalogue classification of this product, when disposed of as waste is

| | | |
|----------------|-----------|---|
| EWC waste code | 08 01 11* | waste paint and varnish containing organic solvents or other dangerous substances |
|----------------|-----------|---|

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

For further information contact your local waste authority.

Disposal recommendations for packaging

Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers.

Empty containers must be scrapped or reconditioned.

Not emptied containers are hazardous waste (waste code number 150110).

SECTION 14: Transport information



Trade name: Marabu-GlasArt 463, 50 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130205463

Replaces Version: 6 / GB

Print date: 10.03.16

Land transport ADR/RID

- 14.1. UN number
UN 1263
- 14.2. UN proper shipping name
PAINT
- 14.3. Transport hazard class(es)
Class 3
Label 3
- 14.4. Packing group
Packing group III
Special provision 640E
Limited Quantity 5 I
Transport category 4
- 14.5. Environmental hazards
-
Tunnel restriction code D/E

Marine transport IMDG/GGVSee

- 14.1. UN number
UN 1263
- 14.2. UN proper shipping name
PAINT
- 14.3. Transport hazard class(es)
Class 3
- 14.4. Packing group
Packing group III
- 14.5. Environmental hazards
no

Air transport ICAO/IATA

- 14.1. UN number
UN 1263
- 14.2. UN proper shipping name
PAINT
- 14.3. Transport hazard class(es)
Class 3
- 14.4. Packing group
Packing group III
- 14.5. Environmental hazards
-

Information for all modes of transport

- 14.6. Special precautions for user
Transport within the user's premises:
Always transport in closed containers that are upright and secure.
Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Other information

- 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code
no

SECTION 15: Regulatory information ***

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Major-accident categories acc. 96/82/EC

| | | | | | | |
|----------|---|-----------|-----------|----|------------|----|
| Category | 6 | Flammable | 5.000.000 | kg | 50.000.000 | kg |
|----------|---|-----------|-----------|----|------------|----|



Trade name: Marabu-GlasArt 463, 50 ml

Version: 7 / GB

Date revised: 14.12.2015

Substance number: 130205463

Replaces Version: 6 / GB

Print date: 10.03.16

VOC ***

| | | | | |
|----------|-------|---|-------|-----|
| VOC (EU) | 34,22 | % | 318,2 | g/l |
|----------|-------|---|-------|-----|

Other information

The product does not contain substances of very high concern (SVHC).

Other information

All components are contained in the TSCA inventory or exempted.

All components are contained in the AICS inventory.

All components are contained in the PICCS inventory.

All components are contained in the DSL inventory.

All components are contained in the ENCS inventory.

15.2. Chemical safety assessment

For this preparation a chemical safety assessment has not been carried out.

SECTION 16: Other information**Hazard statements listed in Chapter 3**

| | |
|--------|---|
| EUH066 | Repeated exposure may cause skin dryness or cracking. |
| H226 | Flammable liquid and vapour. |
| H302 | Harmful if swallowed. |
| H304 | May be fatal if swallowed and enters airways. |
| H312 | Harmful in contact with skin. |
| H319 | Causes serious eye irritation. |
| H332 | Harmful if inhaled. |
| H336 | May cause drowsiness or dizziness. |
| H361d | Suspected of damaging the unborn child. |
| H412 | Harmful to aquatic life with long lasting effects. |

CLP categories listed in Chapter 3

| | |
|-------------------|--|
| Acute Tox. 4 | Acute toxicity, Category 4 |
| Aquatic Chronic 3 | Hazardous to the aquatic environment, chronic, Category 3 |
| Asp. Tox. 1 | Aspiration hazard, Category 1 |
| Eye Irrit. 2 | Eye irritation, Category 2 |
| Flam. Liq. 3 | Flammable liquid, Category 3 |
| Repr. 2 | Reproductive toxicity, Category 2 |
| STOT SE 3 | Specific target organ toxicity - single exposure, Category 3 |

Supplemental information

Relevant changes compared with the previous version of the safety data sheet are marked with: ***

This information is based on our present state of knowledge. However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship.

The information in this Safety Data Sheet is based on the present state of knowledge and current legislation.

It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions.

As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.